



Rotary table

Description

Our tables are made of high density Meehanite, machined to the perfection with high quality CNC machines and inspected at every stage to assure the best quality and accuracy. Excellent quality, made to last. Worm, as well as the rest of key parts, are hardened and grounded. Worm ratio is 90:1, work table is graduated a full 360 degrees so that one turn of the handle moves the table 4 degrees. The micro collar is graduated in steps of 1 min, a vernier scale makes setting down to 10 seconds even possible. Very popular for their excellent performance, quality of their materials, precision, practical design and excellent price. Widely used for circular cutting work, angle setting, boring, spot facing and any similar work. Use excellent machining center to process. Spindle end be applied accuracy bearing. Can be assured to keep very steady under load cutting. Indexing accuracy of direct Indexing mechanism Maximum cumulative spacing error 1 minute.

Extra information

Item number	20112291	
Model	HVRT 254-109	
Model group	HVRT ...	
EAN	8718242070508	
CBS Statistics number	84661020	
Article group	TCE Tooling	
Brand	Huvema	
	A1	106 mm
	D	254 mm
	H	109 mm
	H1	163 mm
	A	321 mm
	B	276 mm
Features	T slot	14 mm
	Bolt slots	17 mm
	Taper	MT3
	Load capacity horizontal	90 kg
	Load capacity vertical	50 kg
	Dimensions	321 x 276 x 109 mm
	Weight	35,5 kg
Article group code	969209	

Product images

