

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



# **Grinding compound**

### **Description**

This oily grinding compound, with sharp-edged SiC grains with grain size 90, is used for fine grinding and slotting of valves & bearings.

#### Suitable for:

- very fine grinding work, e.g. when rotating valve seats, shaft bearings
- as preparation for polishing with felt polishing tools and lapping discs.

#### **Features**

#### **Workable materials:**

Aluminium

Bronze

Stainless steel (stainless steel)

Hardened, heat-treated steels above 1,200 N/mm<sup>2</sup> (< 38 HRC)

Cast steel

Copper

Brass

Cobalt-based alloys

Nickel-based alloys

Titanium

Titanium alloys

Steels with hardness > 54 HRC

Steels up to 1,200 N/mm<sup>2</sup> (< 38 HRC)

**Thermoplastics** 

Fibre-reinforced duroplastics

### **Application:**

polishing

stepwise fine grinding

### **Extra information**

Item number	PF44220090
Model	SFP 90
EAN	4007220153963
CBS Statistics number	34059010
Article group	PFERD
Brand	PFERD
Features	Content 250 gram  Grit size 90
	GHI SIZE 90
Article group code	1317022

## **Product images**





