

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



## Direct driven air compressor

## **Description**

The Huvema HU 500/998 reciprocating compressor; is designed for professionals. However; its features such as reliability, stability and robustness also make it a perfect choice for everyone.

The Huvema HU 500/998 is a perfect solution for intermittent or frequent use and ideal for the needs of inflating, blowing, cleaning, nailing and stapling, professional grinding, gravity painting, hammering, needle rusting, screwing, use of impact spanners and many others.

## **Extra information**

| Item number           | 21294                        |  |
|-----------------------|------------------------------|--|
| Model                 | HU 500-998                   |  |
| EAN                   | 8718242582681                |  |
| CBS Statistics number | 84148022                     |  |
| Article group         | Direct driven air compressor |  |
| Brand                 | Huvema                       |  |

|                    | Air output           | 1070 ltr/min         |
|--------------------|----------------------|----------------------|
|                    | Content tank         | 500 ltr              |
|                    | Pressure max.        | 10 bar               |
|                    | Speed                | 1270 rpm             |
|                    | Drive                | belt                 |
|                    | Number of cylinders  | 2 pcs                |
|                    | Number of pistons    | 2 pcs                |
|                    | Lubrication          | oil                  |
|                    | Filter-reducer       | No                   |
|                    | Ball valve           | yes                  |
| Features           | Condensate drain     | yes, manually        |
|                    | Dimensions b x h x d | 1970 x 590 x 1300 mm |
|                    | Weight               | 260 kg               |
|                    | Color                | RAL 5015             |
|                    | Engine power         | 7.5 kW               |
|                    | Voltage              | 400 V                |
|                    | Frequency            | 50 Hz                |
|                    | Phase                | 3                    |
|                    | Max. current         | 12.0 A               |
|                    | Plug                 | niet aanwezig        |
|                    | Protection class     | IP44                 |
| Article group code | 1601082              |                      |
|                    |                      |                      |

## **Product images**











