

Huvema B.V Kennedylaan 14 5466 AA Veghel Nederland info@huvema.nl Tel +31 413 34 22 75 KVK 16028008 Btw NL003107905B01



## **ProtoTRAK CNC lathe**

### **Description**

The Prototrak CNC is the most user-friendly control for single pieces and small series jobs.

No loss of flexibility compared to a conventional machine.

Reduce your labor costs 4 to 10 times, every time, and always.

No surprises in the options, that's why it's all included as standard:

Free 1 day training for up to 5 people. You do not need to know anything about CNC, only the basis of conventional machining is sufficient.

Free positioning according to DIN8606

Self-centering 3 chuck

Freezer pump installation

Quick change chisel holder with 6 holders

Loose head

Constant cutting speed

Lubrication with joystick

Fully automatic lubrication

Slide-on protective cover and solid rear wall

Fixed centres and adapter bush

Lightening

**TRAKing®** 

#### Options:

No endless list, although these options may be useful for your type of work:

Automatic 4- or 8-way chisel holder

Surface plate

independent 4-chuck

Fixed glasses and/or moving glasses

Off-line software

**DXF** Converter

Transport of the machine and placement on the workplace

Chisels

## **Extra information**

| Item number           | XD17848       |
|-----------------------|---------------|
| Model                 | RLX 780x3000  |
| EAN                   | 8718242478465 |
| CBS Statistics number | 84581900      |
| Article group         | CNC           |
| Brand                 | XYZ           |

| Features           | Swing over bed                             | 780 mm                                |
|--------------------|--|---------------------------------------|
|                    | Distance between centres                   | 3000 mm                               |
|                    | Hole through spindle                       | 160 mm                                |
|                    | Engine power                               | 32 kW                                 |
|                    | Maximum rotation diameter in the bag       | 1090 mm                               |
|                    | Maximum turning diameter above the trolley | 535 mm                                |
|                    | Cross slide travel                         | 430 mm                                |
|                    | Maximum cutting length                     | 2900 mm                               |
|                    | Spindle nose                               | A2-11                                 |
|                    | Uptake of the fixed head                   | MT7 in reducer                        |
|                    | Speed range                                | 20-1300 rpm<br>(vario in 2<br>stages) |
|                    | Movement tail stock taper                  | 200 mm                                |
|                    | Tail stock taper                           | MT6                                   |
|                    | Tail stock taper                           | 105 mm                                |
|                    | Width of bed                               | 500 mm                                |
|                    | Main dimensions LxWxH                      | 5400 x2200<br>x2020 mm                |
|                    | Weight                                     | 8600 kg                               |
|                    | Voltage                                    | 400 V                                 |
| Article group code | 1284477                                    |                                       |

27/11/2024

# **Product images**



