



Welder MMA

Description

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Properties:

compact and light

high welding current stability in spite of mains voltage fluctuations

arc force, hot start and anti-stick devices

thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MMA welding accessories.

Extra information

Item number	T816081	
Model	INFINITY 180 230V ACX	
EAN	8004897967561	
CBS Statistics number	85153918000	
Article group	Products still to be classified	
Brand	TELWIN	
Features	Duty cycle EN60974-1	160@35%
	Weight	6,145 kg
	Max. current	160 A
	Power consumption min. /max.	3,3 - 4,5 kW
	Mains fuse	16 A
	Protection degree	IP23
	Max. voltage empty	60 V
	Absorbed current	23 A
	Min. power generator	7 kW
	Efficiency / factor of power	90%
	MMA electrode diameter	1,6 - 4 mm
	Field control current	20 - 160 A
	Power to 60%	120 A
	Max. current 2	30 A
	Power factor	0,7
Dimensions l x b x h	354 x 145 x 240 mm	
Voltage	230 V	
Article group code	954220	

