



Punching shearing machine

Description

The HKM hydraulic punching machine with shear function is equipped with one double acting cylinder and anti-rotation guide. Round holes can be simply and efficiently made with the standard punch and die holder. The cutting station is used to shorten flat material. Corner iron and bar material can be shortened to the right size.

Finally, rectangles can be cut out quick and easy.

Properties:

Punch holder

Knives for cutting flat, round, square and L-Profile with minimal distortion

Rectangle cutter

1 control pedal

Laying table punch with adjustable stops

Laying table corner cutter with adjustable stops

Punch and die of Ø 25 mm

1 m electromechanical stop

Necessary keys and tools

Machine complies with CE standard

Kingsland 9001

Extra information

Item number	23825	
Model	HU 40 HKM	
EAN	8718242152921	
CBS Statistics number	846249990011	
Article group	Punching shearing machine	
Brand	Huvema	
Features	Punching	Ø20 x 15 mm
	Pressure force	40 ton
	Max. stroke length	50 mm
	Cutting solid round	30 mm
	Cutting solid square	25 mm
	Angle shearing 90°	80 x 80 x 8 mm
	Angle shearing 45°	50 x 6 mm
	Flat steel 1	200 x 13 mm
	Flat steel 2	300 x 6 mm
	Max. notching thickness	nvt
	Max. notching width	nvt
	Max. notching depth	nvt
	Distance spindle-column	175 mm
	Sheet length	356 mm
	Engine power	3 kW
Dimensions. machine l x b x h	1100 x 800 x 1520 mm	
Voltage	400 V	
Weight	580 kg	
Article group code	1076094	

Product images



